

Material Safety Data Sheet

Product: TNT with Protopet 2A Petrolatum USP Simulant, P/N: XM-111-T

Date of Preparation: 12/11/01

12/11/01

TNT Simulant with Protopet 2A Petrolatum, P/N: XM-111-T

MSDS

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Simulant for Trinitrotoluene (TNT), with Petrolatum USP

Chemical Formula: for TNT $C_7H_5N_3O_6$, and a mixture of hydrocarbons refined from petroleum

CAS Number:

Other Designations: Yellow Protopet 2A Petrolatum Simulant with 8% 2,4,6-Trinitrotoluene

General Use: To have the vapor signature of an explosive, but will not explode.

Manufactured for: XM division of Van Aken International, 9157 Rochester Court, Rancho Cucamonga, CA 91730,
TEL (909) 980-2001, FAX (909) 980-2333 (hours 8:00am till 4:30pm of operation), emergency TEL (909) 260-2561.

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Section 2 - Composition / Information on Ingredients

Ingredient Name	CAS Number	% wt
Petrolatum USP	8009-03-6	>92%
2,4,6-Trinitrotoluene	118-96-7	<8%

Trace Impurities: May contain 1.0 ppm Butylated Hydroxytoluene as stabilizer

Ingredient	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH IDLH
	TWA	STEL	TWA	STEL	TWA	STEL	
Petrolatum USP	5 mg/m ³	none estab.	none estab.	none estab.	none estab.	none estab.	none estab.
TNT	1500mg/m ³ (SKIN)	none estab.	none estab.	none estab.	none estab.	none estab.	none estab.

Toxicity Data: Exposure Limits 0.1 mg/m³ (resp), 1.5 mg/m³ (skin), 500 mg/24H MLD(skn-rbt), 500 mg/ 1H MLD (eye-rbt)

Section 3 - Physical and Chemical Properties

Physical State: semi-solid

Appearance and Odor: opaque, white to amber and no odor

Odor Threshold: None

Density: slightly less than 1 gm/cc

Specific Gravity (H₂O=1, at 4 °C):.95

pH: not applicable

Water Solubility: nil

Other Solubilities:

Melting Point: 38 to 60^o C (240^oc for TNT)

Evaporation Rate: 0 at 25^oC

Vapor Pressure (mm Hg at 20^oc): less than .0005

Section 4 - Fire-Fighting Measures

Flash Point: greater than 204^oC

Burning Rate:

Autoignition Temperature: none

LEL: N/A

UEL: N/A

Flammability Classification: 94 V-1

Extinguishing Media: Dry chemical or Water fog or CO₂ or Foam or Sand/earth. Closed containers exposed to fire may be cooled with water

Unusual Fire or Explosion Hazards: none

Hazardous Combustion Products: CO, CO₂, NO, Carbon monoxide and carbon dioxide from burning

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways. Water spray is an unsuitable extinguishing agent.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

Section 5 - Stability and Reactivity

Stability: Product is stable at room temperature in closed containers under normal storage and handling conditions.

12/11/01

TNT Simulant with Yellow Protopet 2A Petrolatum, P/N: XM-111-T

MSDS

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong oxidizers such as hydrogen peroxide, bromine, and chromic acid.

Conditions to Avoid: none known

Hazardous Decomposition Products: none

Section 6 - Health Hazard Information

Potential Health Effects

Primary Entry Routes: Under normal conditions no absorption through the skin. By inhalation or other route of entry is anticipated. If used in applications where a mist may be generated, observe a TWA/PEL of 5 mg/m³ for mineral oil mist (OSHA and ACGIH).

Target Organs: eyes, skin, lungs, nervous system, bone marrow

Acute Effects: no data available

Inhalation: Respiratory tract irritation, convulsions, and unconsciousness

Eye: irritation

Skin:

Ingestion: Headache, fall in blood pressure, methemoglobinemia

Carcinogenicity: IARC, NTP, and OSHA do not list product or chemical as a carcinogen.

Medical Conditions Aggravated by Long-Term Exposure: Petrolatum USP grades are fully refined materials meeting the requirements of the United States Pharmacopeia XXII and the requirements of the Food and Drug Administration as per Title 21 CFR parts 172.880 and 178.3700.

Chronic Effects: no data available

Emergency and First Aid Procedures

Inhalation: not applicable

Eye Contact: For molten product only, immediately flush with large quantities of water for at least 15 minutes and call a physician.

Skin Contact: If burned by contact with hot material, cool burned skin area as quickly as possible by immersing in cold water, or applying cold water. Call a physician

Ingestion: Contact a physician

After first aid, get appropriate in-plant, paramedic, or community medical support.

Note to Physicians: TNT is vasodilator like other nitrate esters

Special Precautions/Procedures:

Section 7 - Spill, Leak, and Disposal Procedures

Spill /Leak Procedures: Shut off leak and dike up large spills. After cooling and solidification, scrape and/or shovel up material. Finally, clean area with an oil absorbent material. Dispose of material as a non explosive waste.

Small Spills: Same

Large Spills: Same

Containment: For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

Cleanup: Do not use acetone, use water as necessary.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Disposal Regulatory Requirements: As an inert material.

Container Cleaning and Disposal: Use water.

Ecological Information: None

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification (40 CFR 261.): Not classified

CERCLA Hazardous Substance (40 CFR 302.4) unlisted specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

CERCLA Reportable Quantity: none known

SARA 311/312 Codes: none known

SARA Toxic Chemical (40 CFR 372.65): Not listed

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed.

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed

OSHA Specifically Regulated Substance (29CFR 1910.109)

State Regulations: Same

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: Handle as an inert material.

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. ̂2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls: Maintain in approved storage area.

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA.

Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses. Handle behind a barrier.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Special Precautions and Comments

Handling Precautions: If product will normally be maintained in a heated, liquid form, exercise suitable precautions to avoid thermal burns. Avoid breathing mist or vapors.

Storage Requirements: Maximum storage temperature 38°C

DOT Transportation Data (49 CFR 172.101):

Shipping Name: TNT Simulant,
not an explosive

Shipping Symbols: none

Hazard Class: not applicable

ID No.:

Packing Group:

Label:

Special Provisions: Petrolatum

Packaging Authorizations

a) **Exceptions:** none

b) **Non-bulk Packaging:** none

c) **Bulk Packaging:** none

Quantity Limitations

a) **Passenger, Aircraft, or Railcar:** none

b) **Cargo Aircraft Only:** none

Vessel Stowage Requirements

a) **Vessel Stowage:** none

b) **Other:**

Prepared By: B. MacDonald

Revision Notes: RVA 1/29/08

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.